PREMIER FINISHES

Safety Data Sheet
10-661 * EnviroTech Gloss - Machine Grey

SECTION 1: Identification

1.1 GHS Product identifier

Product name	10-661 * EnviroTech Gloss TopCoat - Machine Grey
Brand	Endura-Clad Coatings, Inc.
Product Names (aka)	'Endura-Plate', 'Endura-Plate - Ultra-Durable Acrylic Enamel'

1.2 Other means of identification

Tinted Self XLink Sealer
EnduraPlate
All Purpose TopCoat

1.3 Recommended use of the chemical and restrictions on use

Ultra durable self-crosslinking acrylic enamel for commercial, industrial and architectural applications. Waterbourne, quick drying with a very hard finish. Low VoC. Low odor. Suitable for both interior and exterior applications. Ideal for high-traffic areas and projects requiring quick turnaround with a hard wearing surface.

1.4 Manufacturer Manufactured under contract for Endura-Clad Coatings, Inc.

Name	Premier Finishes
Address	17890 NW Airport Way #155 Portland OR 97230 USA
Telephone	(503) 241-2770
email	office@premierfinishes.net

1.5 Emergency phone number 1-800-262-8200

SECTION 2: Hazard identification

General hazard statement

Not a hazardous substance or mixture.

2.1 Classification of the substance or mixture

GHS classification in accordance with: OSHA (29 CFR 1910.1200)

Not a hazardous substance or mixture.

2.2 GHS label elements, including precautionary statements

Not a hazardous substance or mixture.

2.3 Other hazards which do not result in classification

Not a hazardous substance or mixture.

SECTION 3: Composition/information on ingredients

3.1 Mixtures

Any concentration shown as a range is to protect confidentiality or due to batch variation.

Hazardous components

Component	CAS no.	Concentration
Not Regulated - Non Hazardous		**> 60 - < 70 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Water (EC no.: 231-791-2)	**7732-18-5**	**> 15 - < 20 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Titanium(IV) oxide (EC no.: 236-675-5; Index no.: 022-006-00-2)	**13463-67-7**	**> 5 - < 10 % (weight)**
CLASSIFICATIONS: Carcinogenicity (C.4.9), Cat. 2. HAZARDS: H351 - Suspected of causing cancer [route].		
Texanol (EC no.: 246-771-9)	**25265-77-4**	**> 3 - < 5 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Propylene glycol (EC no.: 200-338-0)	**57-55-6**	**> 0.5 - < 1 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Butoxyethanol (EC no.: 203-905-0; Index no.: 603-014-00-0)	**111-76-2**	**> 0.1 - < 0.5 % (weight)**
CLASSIFICATIONS: Acute toxicity, inhalation (C.4.3), Cat. 3; Acute toxicity, oral (C.4.1), Cat. 4; Skin corrosion/irritation (C.4.4), Cat. 2; Eye damage/irritation (C.4.5), Cat. 2A. HAZARDS: H302 - Harmful if swallowed; H315 - Causes skin irritation; H319 - Causes serious eye irritation; H331 - Toxic if inhaled. [SCLs/M-factors/ATEs]: inhalation:; ATE = 3 mg/L (Vapours); oral:; ATE=1 200 mg/kg bw		
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl- (EC no.: 204-809-1)	**126-86-3**	**> 0.1 - < 0.5 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Carbon black (airborne, unbound particles of respirable size) (EC no.: 215-609-9)	**1333-86-4**	**> 0.1 - < 0.5 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Poly(oxy-1,2-ethanediyl), alpha-(phenylmethyl)-omega-[(1,1,3,3-tetramethylbutyl)phenoxy]-	**60864-33-7**	**> 0.1 - < 0.5 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Bentonite (< 2% crystalline silica) (EC no.: 215-288-5)	**1302-78-9**	**> 0.05 - < 0.1 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether	**9038-95-3**	**> 0.01 - < 0.05 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Polyethylene glycol mono(tert-octylph-enyl) ether9036-19-5	**9036-19-5**	**> 0.01 - < 0.05 % (weight)**
CLASSIFICATIONS: No data available. HAZARDS: No data available.		
Alcohols, C10-16, ethoxylated (EC no.: 500-182-6)	**68002-97-1**	**> 0.01 - < 0.05 % (weight)**
CLASSIFICATIONS: Acute toxicity, oral (C.4.1), Cat. 4; Eye damage/irritation (C.4.5), Cat. 1; Skin corrosion/irritation (C.4.4), Cat. 2. HAZARDS: H302 - Harmful if swallowed; H315 - Causes skin irritation; H318 - Causes serious eye damage.		
Silica, crystalline (EC no.: 238-878-4)	**14808-60-7**	**> 0.005 - < 0.01 % (weight)**
CLASSIFICATIONS: Carcinogenicity (C.4.9), Cat. 1A; Specific target organ toxicity (repeated exposure) (C.4.12), Cat. 1. HAZARDS: No data available.		

SECTION 4: First-aid measures

4.1 Description of necessary first-aid measures

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
If inhaled	If inhaled: Call a poison center or doctor if you feel unwell. Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
In case of skin contact	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor. Wash contaminated clothing before reuse. Acute and delayed symptoms and

	effects: May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
In case of eye contact	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Acute and delayed symptoms and effects: Causes serious eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
If swallowed	If swallowed: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Acute and delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

SECTION 5: Fire-fighting measures

5.1 Suitable extinguishing media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

5.2 Specific hazards arising from the chemical
Closed containers may rupture if exposed to fire or extreme heat.

Texanol: Carbon oxides

Magnesium nitrate: Nitrogen oxides (NOx)

5-chloro-2-methyl-3(2H)-isothiazolone: carbon dioxide, carbon monoxide, hydrogen sulfide, nitrogen oxides, phosgene

-----
Bentonite (< 2% crystalline silica): Aluminum oxide, silicon oxide

5.3 Special protective actions for fire-fighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

6.2 Environmental precautions
Keep out of drains, sewers, ditches, and waterways.

6.3 Methods and materials for containment and cleaning up
Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Keep out of the reach of children. Do not Freeze.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

CAS: (not specified)
Titanium(IV) oxide
US/OSHA (US): 5 mg/m3 (Resp), 15 mg/m3 (Total) PEL inhalation [Titanium dioxide]

CAS: 111-76-2
Butoxyethanol
AU/SWA (AU): 50 ppm; 242 mg/m3 STEL inhalation [2-Butoxyethanol]; 20 ppm; 96.9 mg/m3 TWA inhalation [2-Butoxyethanol]; Cal/OSHA (US): 20 ppm, 97 mg/m3 PEL inhalation [2-Butoxyethanol]; 20 ppm PEL inhalation [2-Butoxyethanol]; EU/OSHA (EU): 98 mg/m3 IOELV-LTEL inhalation [2-butoxyethanol]; 20 ppm IOELV-LTEL inhalation [2-butoxyethanol]; 246 mg/m3 IOELV-STEL inhalation [2-butoxyethanol]; 50 ppm IOELV-STEL inhalation [2-butoxyethanol]; NIOSH (US): 5 ppm REL inhalation [2-Butoxyethanol]; 5 ppm, 24 mg/m3 TWA inhalation [2-Butoxyethanol]; US/OSHA (US): 50 ppm PEL inhalation [2-Butoxyethanol]; 240 mg/m3 PEL inhalation [2-Butoxyethanol]; 50 ppm, 240 mg/m3 TWA inhalation [2-Butoxyethanol]

CAS: 1333-86-4
Carbon black (airborne, unbound particles of respirable size)
AU/SWA (AU): 3 mg/m3 TWA inhalation [Carbon black]; Cal/OSHA (US): 3.5 mg/m3 PEL inhalation [Carbon black]; NIOSH (US): 3.5 mg/m3 (without PAHs); when PAHs are present, NIOSH considers carbon black to be a potential occupational carcinogen., See Appendix A, See Appendix C REL inhalation [Carbon black]; US/OSHA (US): 3.5 mg/m3 PEL inhalation [Carbon black]

CAS: 13463-67-7
Titanium(IV) oxide
AU/SWA (AU): 10 mg/m3 TWA inhalation [Titanium dioxide]; Cal/OSHA (US): See PNOR PEL inhalation [Titanium dioxide - Total dust]; NIOSH (US): Ca, (ultrafine particles), 2.4 mg/m3 (fine), 0.3 mg/m3 (ultrafine), See Appendix A, See NIOSH Intelligence Bulletin 63 REL inhalation [Titanium dioxide - Total dust]; US/OSHA (US): 15 mg/m3 PEL inhalation [Titanium dioxide - Total dust]

CAS: 14808-60-7
Silica, crystalline
AU/SWA (AU): 0.05 mg/m3 TWA inhalation [Quartz (respirable dust)]; Cal/OSHA (US): 0.05 mg/m3, (See Sections 1532.3 & 5204) PEL inhalation [Quartz: see 1910.1053(m)]; NIOSH (US): Ca, 0.05 mg/m3, See Appendix A REL inhalation [Quartz: see 1910.1053(m)]

CAS: 57-55-6
Propylene glycol
AU/SWA (AU): 150 ppm; 474 mg/m3 TWA inhalation [Propane-1,2-diol total: (vapour & particulates)]; 10 mg/m3 TWA inhalation [Propane-1,2-diol: particulates only]; US/OSHA (US): 10 mg/m3 TWA inhalation

8.2 Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8.3 Individual protection measures, such as personal protective equipment (PPE)

Pictograms

Eye/face protection
Wear safety glasses

Skin protection
Wear protective gloves

Body protection
Wear suitable protective clothing.

Respiratory protection
Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Environmental exposure controls
Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Basic physical and chemical properties

Physical state	Liquid
Appearance	Dk Grey
Odor	Slight Apple
Flash point	Not Combustible
pH	8.3 - 9.3
Solubility	Water
Spec. Gravity	1.11
Solids Vol %	32.38%
Solids Wt%	39%
Material VoC:	0.49
Coating VoC:	1.27
Spread @ 1 Mil:	519.3726

SECTION 10: Stability and reactivity

10.1 Reactivity
No specific test data related to reactivity is available for this product or its ingredients.

10.2 Chemical stability
Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions
Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous polymerization does not occur.

10.4 Conditions to avoid
Do not store in direct sunlight.
Do not freeze.
Do not ingest.

10.5 Incompatible materials

Dipropylene glycol monomethyl ether: Strong oxidizing agents, Strong acids

-----
5-chloro-2-methyl-3(2H)-isothiazolone: strong oxidizing agents

-----
Propylene glycol: Acid chlorides, Acid anhydrides, Oxidizing agents, Chloroformates, Reducing agents

-----
Silica, crystalline : Hydrogen fluoride

10.6 Hazardous decomposition products

Water: In the event of fire: see section 5

Dipropylene glycol monomethyl ether: Hazardous decomposition products formed under fire conditions. - Carbon oxides
Other decomposition products - No data available
In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity
Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Symptoms (including delayed and immediate effects):
Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing,nasal discharge, headache, hoarseness, and nose and throat pain.
Ingestion: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.
Eye: see below.
Skin: see below.

Skin corrosion/irritation
May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Serious eye damage/irritation
May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Respiratory or skin sensitization
No data available.

Germ cell mutagenicity
No data available.

Carcinogenicity
This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity
No data available.

Specific target organ toxicity (STOT) - single exposure
No data available.

Specific target organ toxicity (STOT) - repeated exposure
No data available.

Aspiration hazard
No data available.

Additional information

Texanol: Organism Test Type Route Reported Dose (Normalized Dose) Effect Source
guinea pig LD skin > 20mL/kg (20mL/kg) Kodak Company Reports. Vol. M-158E, Pg. 1981,
mouse LD50 oral 3200mg/kg (3200mg/kg) Kodak Company Reports. Vol. M-158E, Pg. 1981,
rat LC inhalation > 3500mg/m3/6H (3500mg/m3) Kodak Company Reports. Vol. 21MAY1971,
rat LD50 oral 3200mg/kg (3200mg/kg) Kodak Company Reports. Vol. M-158E, Pg. 1981,
-----
Titanium(IV) oxide : *TOXICITY:
typ. dose mode specie amount units other
Not available

*AQTX/TLM96: Not available

*SAX TOXICITY EVALUATION:
THR: An experimental carcinogen, neoplastigen and tumorigen. A human skin
irritant. A common air contaminant and nuisance dust.

*CARCINOGENICITY:
Tumorigenic Data:
TCLo: ihl-rat 250 mg/m3/6H/2Y-I

TDLo: ims-rat 360 mg/kg/2Y-I
TD : ims-rat 260 mg/kg/84W-I
Review: IARC Cancer Review: Human Inadequate Evidence
IARC Cancer Review: Animal Limited Evidence
IARC: Not classifiable as a human carcinogen (Group 3) [610]
Status: NCI Carcinogenesis Bioassay (Feed); Negative: Male and Female Rat, Male and Female Mouse [015,620]

*MUTATION DATA: Not available

*TERATOGENICITY: Not available

*STANDARDS, REGULATIONS & RECOMMENDATIONS:
OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z
Transitional Limit: PEL-TWA 15 mg/m3 (total dust) [015,327,545,610]
Final Limit: PEL-TWA 10 mg/m3 (total dust) [015,545,610]
ACGIH: TLV-TWA 10 mg/m3 (for total dust containing no asbestos and less than 1% crystalline silica) [610]
NIOSH: None
NFPA Hazard Rating: Health (H): None
Flammability (F): None
Reactivity (R): None

*OTHER TOXICITY DATA:
Skin and Eye Irritation Data:
skn-hmn 300 ug/3D-I MLD
Status: EPA TSCA Chemical Inventory, 1986
EPA Genetox Program 1988, Negative: Carcinogenicity-mouse/rat; Cell transform.-SA7/SHE
EPA TSCA Section 8(e) Status Report 8EHQ-1083-0497
EPA TSCA Test Submission (TSCATS) Data Base, September 1989

Butoxyethanol: *TOXICITY:
typ. dose mode specie amount units other
TCLo ihl hmn 195 ppm/8H
LD50 orl rat 1480 mg/kg
LC50 ihl rat 450 ppm/4H
LD50 ipr rat 220 mg/kg
LD50 ivn rat 340 mg/kg
LD50 orl mus 1230 mg/kg
LC50 ihl mus 700 ppm/7H
LD50 ipr mus 536 mg/kg
LDLo scu mus 500 mg/kg
LD50 ivn mus 1130 mg/kg
LD50 orl rbt 320 mg/kg
LD50 skn rbt 490 mg/kg
LD50 ivn rbt 280 mg/kg
LD50 orl gpg 1200 mg/kg
LD50 skn gpg 230 mg/kg
LD50 ipr rbt 220 mg/kg

*AQTX/TLM96: 1000-100 ppm

*SAX TOXICITY EVALUATION:
THR = HIGH human irritant via inhalation. HIGH via intravenous, oral and dermal routes. MODERATE via oral, intraperitoneal, inhalation,

subcutaneous and dermal routes. MILD skin and eye irritant.

*CARCINOGENICITY: Not available

*MUTATION DATA:
test lowest dose | test lowest dose
----------- ----------------- | ------------ -----------------
Not available |

*TERATOGENICITY:
Reproductive Effects Data:
TCLo: ihl-rat 200 ppm/6H (6-15D preg)
TCLo: ihl-rat 25 ppm/6H (6-15D preg)
TDLo: orl-mus 9440 mg/kg (7-14D preg)
TCLo: ihl-rbt 200 ppm/6H (6-18D preg)
TCLo: ihl-rbt 100 ppm/6H (6-18D preg)

*STANDARDS, REGULATIONS & RECOMMENDATIONS:
OSHA: Federal Register (1/19/89) and 29 CFR 1910.1000 Subpart Z
Transitional Limit: PEL-TWA 50 ppm (skin) [610]
Final Limit: PEL-TWA 25 ppm (skin) [610]
ACGIH: TLV-TWA 25 ppm (skin) [610]
NIOSH Criteria Document: None
NFPA Hazard Rating: Health (H): 2
Flammability (F): 2
Reactivity (R): 0
H2: Materials hazardous to health, but areas may be entered freely with
full-faced mask self-contained breathing apparatus which provides
eye protection (see NFPA for details).
F2: Materials which must be moderately heated before ignition will occur
(see NFPA for details).
R0: Materials which are normally stable even under fire exposure conditions
and which are not reactive with water (see NFPA for details).

*OTHER TOXICITY DATA:
Skin and Eye Irritation Data:
skn-rbt 500 mg open MLD
eye-rbt 18 mg
Standards and Regulations: DOT-IMO: Poison B; Label: St. Andrew's Cross,
Flammable liquid
Status: "NIOSH Manual of Analytical Methods, 3rd. Ed."
Reported in EPA TSCA Inventory, 1983
EPA TSCA Section 8(e) Status Report 8EHQ-0483-0475
Meets criteria for proposed OSHA Medical Records Rule

Silica, crystalline : The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity.
Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential.
Liver - Irregularities - Based on Human Evidence
Lungs - Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung

tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP. - Based on Human Evidence

SECTION 12: Ecological information

Persistence and degradability

Bioaccumulative potential

Bioaccumulative (B)?	No

Mobility in soil
No data available

Results of PBT and vPvB assessment
No data available

Endocrine disrupting properties
No data available

SECTION 13: Disposal considerations

Disposal methods

Product disposal
Dispose of contents/containers in accordance with local regulations.

Packaging disposal
Do not reuse empty containers.

SECTION 14: Transport information

DOT (US)
Not dangerous goods

IMDG
Not dangerous goods

IATA
Not dangerous goods

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

California Prop. 65 components
Chemical name: Carbon black (airborne, unbound particles of respirable size)
CAS number: 1333-86-4
02/21/2003 - Cancer

California Proposition 65 Chemicals List
WARNING: This product can expose you to chemicals including Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Canadian Domestic Substances List (DSL)
Chemical name: Water
CAS number: 7732-18-5

Chemical name: Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol
CAS number: 25265-77-4

Chemical name: Titanium oxide (TiO2)
CAS number: 13463-67-7

Chemical name: 1,2-Propanediol
CAS number: 57-55-6

Chemical name: Ethanol, 2-butoxy-
CAS number: 111-76-2

Chemical name: 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-
CAS number: 126-86-3

Chemical name: Carbon black
CAS number: 1333-86-4

Chemical name: Poly(oxy-1,2-ethanediyl), α-(phenylmethyl)-ω-[(1,1,3,3-tetramethylbutyl)phenoxy]-
CAS number: 60864-33-7

Chemical name: Bentonite
CAS number: 1302-78-9

Chemical name: Oxirane, methyl-, polymer with oxirane, monobutyl ether
CAS number: 9038-95-3

Chemical name: Poly(oxy-1,2-ethanediyl), α-[(1,1,3,3-tetramethylbutyl)phenyl]-ω-hydroxy-
CAS number: 9036-19-5

Chemical name: Alcohols, C10-16, ethoxylated
CAS number: 68002-97-1

Chemical name: Quartz (SiO2)
CAS number: 14808-60-7

EU Cosmetics Allowed Colorants List, (EC) 2009/1223 Annex IV
Chemical name: Titanium(IV) oxide
CAS number: 13463-67-7

EU Cosmetics Restricted Substances List, (EC) 2009/1223 Annex III
Chemical name/INN: Butoxyethanol
CAS number: 111-76-2

EU Table of Harmonised Entries (Annex VI to CLP)
Chemical name: Titanium(IV) oxide
CAS number: 13463-67-7

Chemical name: Butoxyethanol
CAS number: 111-76-2

Massachusetts Right To Know Components (105 CMR 670)
Chemical name: TIN DIOXIDE DUST
CAS number: 13463-67-7
Asterisk: yes; Refs: 2,4

Chemical name: 2-BUTOXYETHANOL
CAS number: 111-76-2
Asterisk: no; Refs: 2,4,6 F8

Chemical name: CARBON BLACK
CAS number: 1333-86-4
Asterisk: no; Refs: 2,4 F5

Chemical name: QUARTZ
CAS number: 14808-60-7
Asterisk: no; Refs: 1,2,4 *E*C* F5

New Jersey Right To Know Components
Common name: TITANIUM DIOXIDE
CAS number: 13463-67-7

Common name: PROPYLENE GLYCOL
CAS number: 57-55-6

Common name: 2-BUTOXY ETHANOL
CAS number: 111-76-2
Listing note: CA-carcinogen; F2-flammable 2nd deg.

Common name: CARBON BLACK
CAS number: 1333-86-4
Listing note: CA-carcinogen.

Common name: SILICA, QUARTZ
CAS number: 14808-60-7
Listing note: CA-carcinogen.

Pennsylvania Right To Know Components
Chemical name: TITANIUM OXIDE (TIO2)
CAS number: 13463-67-7

Chemical name: 1,2-PROPANEDIOL
CAS number: 57-55-6

Chemical name: ETHANOL, 2-BUTOXY-
CAS number: 111-76-2

Chemical name: CARBON BLACK
CAS number: 1333-86-4

Chemical name: QUARTZ (SIO2)
CAS number: 14808-60-7

SARA 302 Components
No chemicals in this material [Propylene glycol] are subject to the reporting requirements of SARA Title III, Section 302.

No chemicals in this material [Butoxyethanol] are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Hazards
No SARA Hazards for: Propylene glycol.

Fire Hazard, Acute Health Hazard, Chronic Health Hazard for: Butoxyethanol.

SARA 313 Components
This material [Propylene glycol] does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

The following components are subject to reporting levels established by SARA Title III, Section 313:
Ethylene glycol monobutyl ether
CAS: 111-76-2 for: Butoxyethanol.

US EPA TSCA public inventory
Chemical name: Water
CAS number: 7732-18-5

Chemical name: Texanol
CAS number: 25265-77-4

Chemical name: Titanium(IV) oxide
CAS number: 13463-67-7

Chemical name: Propylene glycol
CAS number: 57-55-6

Chemical name: Butoxyethanol
CAS number: 111-76-2

Chemical name: 5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-
CAS number: 126-86-3

Chemical name: Carbon black (airborne, unbound particles of respirable size)
CAS number: 1333-86-4

Chemical name: Poly(oxy-1,2-ethanediyl), alpha-(phenylmethyl)-omega-[(1,1,3,3-tetramethylbutyl)phenoxy]-
CAS number: 60864-33-7

Chemical name: Bentonite (< 2% crystalline silica)
CAS number: 1302-78-9

Chemical name: Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether
CAS number: 9038-95-3

Chemical name: Polyethylene glycol mono(tert-octylph-enyl) ether9036-19-5
CAS number: 9036-19-5

Chemical name: Alcohols, C10-16, ethoxylated
CAS number: 68002-97-1

Chemical name: Silica, crystalline
CAS number: 14808-60-7

HMIS Rating

10-661 * EnviroTech Gloss TopCoat - Machine Grey	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

NFPA Rating



SECTION 16: Other information

16.1 Further information/disclaimer

While the description, data, and information contained herein are presented in good faith and believed to be accurate, it is provided for guidance only. Because many factors may affect application/use, it is recommended that you conduct tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding the product described, data, or information set forth, or that the product, data, or information may be used without infringing the intellectual property rights of others. In no case shall the description, information, or data provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree that the description, data, and information furnished herein are provided gratis and we assume no obligation or liability for the description, data, and information given or results obtained, all such being given and accepted at your risk. The content of this SDS (a.k.a. MSDS) is copyrighted [(c) PFI]. This SDS may be shared without changes, and no changes to the PFI content are authorized. Updates to all PFI SDS documents must be obtained directly from PFI. See Section 1 for PFI contact and website information.