

### GENERAL DESCRIPTION

Valspar Metal Building Roof & Siding Finish restores old, weathered metal siding and roofs to a beautiful appearance and protects against rust. This premium water reducible acrylic formula dries quickly to a long lasting, durable, fade and chalk resistant semi-gloss finish. Cleans up easily with soapy and water. Ideal for sloped metal roofs and vertical metal siding on sheds, outbuildings, barns and pole buildings. Use as-is for a "Direct to Metal" (DTM) product or use with Valspar Rusty Metal Primer over corroded metals.

### PRODUCT FEATURES

- Resists rust and corrosion
- 100% acrylic formula dries quickly
- Fade and chalk resistant
- Cleans up with soap and water

### RECOMMENDED USES

Properly prepared, sloped, exterior-metal roofs and vertical-metal siding including steel and galvanized raised ridge. Suitable for wood siding too. Not intended to fix leaking roofs; not for use on flat roofs or nonmetallic roofing materials. Ideal for metal barns, sheds, exterior walls, trim and doors, aluminum siding and mobile homes.

### SHIPPING AND PACKAGING

**Freight Classification:** Paint or paint related material. Protect from freezing.

**Packaging:**

- Gallon – 4 per carton
- 5 gallon pail

### COMPOSITION

**Base and Fill Levels**

	(oz./gal.)
<b>Brite White</b> (4260)	128
<b>Classic Green</b> (4261)	128
<b>Classic Red</b> (4262)	128

### APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply paint with an airless sprayer. Work quickly as paint dries fast on roofing surfaces. Premium-quality polyester brushes and rollers may be used for small or difficult-to-spray areas. **Apply 2 coats to all surfaces; allow to dry overnight between coats.** When applying to raised ridge or other directional surfaces, spray the second coat from the opposite side of the first to ensure complete coverage.

**Airless Spray:**

- Pressure: 2000 PSI
- Tip: 0.017–0.021"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8–1/2" nap

**Thinning:** Thin only for spray application with up to 8 oz. of water per gallon of paint (236 mL per 3.78 L).

### SYSTEM

#### RECOMMENDATIONS

**Galvanized Metal and Aluminum:**

- 1 Coat: Valspar® Galvanized Metal Primer
- 1–2 Coats: Metal Building Siding & Roof Finish

**Ferrous Metal:**

- 1 Coat: Valspar® Anti-Rust Primer
- 1–2 Coats: Metal Building Siding & Roof Finish

**Wood:**

- 1 Coat: Valspar® Exterior Oil or Latex Primer
- 1–2 Coats: Metal Building Siding & Roof Finish

### PRODUCT SPECIFICATIONS

**Vehicle Type:** Acrylic resin

**Pigment Type:**

- White* – Titanium dioxide
- Green* – Thalo green and iron oxide
- Red* – Titanium dioxide, iron oxide and organic red

**Viscosity:** 94–100 Krebs Units

**Sheen:** 25–40 Units @ 60° angle

**Flashpoint:** N/A

**VOC (g/L):** less than 150 g/L

**Volume Solids:** 26–30%

**Weight Solids:** 32–43%

**Weight Per Gallon:**

- White* – 10.1 lbs./gal.
- Green and Red* – 8.9 lbs./gal.

**Practical Coverage:** Covers up to 300 sq. ft. per gallon (28 m<sup>2</sup> per 3.78 L) on raised ridge surfaces

**Recommended Film Thickness:**

- 5.3 mil Wet
- 1.5 mil Dry

**Dry Time @ 77 °F and 50% Relative Humidity**

**To The Touch:** 30–60 minutes

**Recoat:** overnight

**Application Temperature:** 50–90 °F (10–32 °C)

### REGULATORY COMPLIANCE

Current as of: 7/17/2018

SCAQMD	No
CARB 2000 SCM	Yes
CARB 2007 SCM	No
OTC/LADCO	Yes
US National	Yes

### CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

#### SURFACE PREPARATION

##### **General:**

Read the Lead Warning paragraph. **Thoroughly clean the surface and allow to dry.** Inspect roof and siding seams for leaks and make repairs with appropriate paintable patching material. Remove all wax, grease, dirt, chalk, mildew, loose and peeling paint, rust and other foreign matter. New or bare surfaces should be primed with an appropriate Valspar® primer.

##### **Mildew:**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

##### **Wood/Bare Wood:**

Remove sap from knots and sappy areas. Spot prime knots with a Valspar® exterior oil-based primer. Then prime new or bare surfaces with a Valspar® exterior latex or oil primer.

##### **Ferrous Metal (Steel and Iron):**

Hand or power tool clean steel to remove loose mill scale and rust. For large areas, cleaning is most effective with a power washer. Remove oily residues and contaminants with solvent or appropriate cleaning solution. Change rags often, to assure that residual contaminants are completely removed. Prime with Valspar® Armor Anti-Rust Primer.

##### **Galvanized Metal and Aluminum:**

Allow new galvanized metal to age six months or clean with mild muriatic solution. Metal should be free of oils and other contaminants. Prime with Valspar® Armor Anti-Rust Primer.

#### LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

#### LIMITED WARRANTY

This product is warranted to meet the application, appearance and performance properties stated on the label. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous paint. **If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund.** THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

#### CAUTIONS

4264, 4265: CAUTION! Contains: dipropylene glycol n-butyl ether.

4260, 4261, 4262: WARNING! Contains: dipropylene glycol n-butyl ether and crystalline Silica.

**All: KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY.

4260, 4261, 4262: Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. WARNING: This product contains a chemical known to the State of California to cause cancer.

**All: First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

4264, 4265: UCL 1.1

4260, 4261, 4262: UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

8725 W. Higgins Rd., Chicago, IL 60631

877.825.7727

valsparpaint.com

Revised: 7/17/18

Version: 4260C